

Automatic Skinner D3000


Automatic skinner with high production capacity.



- Adjustable cut from 2 to 6mm.
- Complete stainless steel construction.
- Easy cleaning.
- Electric operation, does not need air.
- Floating blade holder.
- Protection of double opening.
- Adjustable belt height.

Dimensions

LENGTH(A): HEIGHT (G): HEIGHT TO BELT (D): WIDTH(B): WEIGHT: 1800mm. 1250mm. 915mm. 750mm. 180Kg.



Technical data

POWER:
CONVEYOR BELT WIDTH:
BLADE CUTTING WIDTH:
PRODUCTION:
OPERATION:
BLADE HOLDER PRESSURE:
GUMS PRESSURE:

ICv (0.75kw)
420m.
447m.
TO GDODKG/H WITH AN OPERATOR
TOTALLY ELECTRIC
SPRING
PROGRESSIVE SPRING

SAFETY:

TRANSMISSION:
ANGLE OF OUTPUT BELTS:
PROTECTION OF DOUBLE OPENING:

SAFETY CONTACT
LID OPENING ACCORDING TO
THE CE STANDARDS
CHAIN
ADJUSTABLE HEIGHT





The protection of double opening allows easy and safe access.



the conic attacking gums tense the piece for an optimum peeling.



The outlet conveyor belt is adjustable in height to fit any table.



D3000 uses a floating blade holder system that allows a perfect fitting to any piece.

Other formats

D3000-HAM

For peeling of cured ham, with specific gum drags and protection with greater height.

Adjustments

- Adjustable cut from 2 to 6mm.
- Gums height.
- Height adjustment of the outlet conveyor belt.
- Millimetric adjustment of blade position.



The D3000-HAM is very effective for polishing cured ham. It improves processing time and minimizes losses.
The perfect tandem with the handheld skinner LAINT.



Abad Maquinaria Industrial S.L. C/Roure Gros 31 - 08181 Sentmenat (Barcelona) ESPAÑA Telf: 93 715 45 13 Fax: 93 715 45 65 laint@laint.net - www.laint.es



